

# SPACE WEATHER AND SATELLITE COMMUNICATIONS: AN USEFUL SYNERGY BETWEEN GEOPHYSICISTS AND ENGINEERS

**J.B. Destro-Filho<sup>(1)</sup>, E. R. de Paula<sup>(2)</sup>, F.S. Rodrigues<sup>(3)</sup>, D.W. Matolak<sup>(4)</sup> and A.P. Soares<sup>(5)</sup>**

<sup>(1)</sup> *DECOM/FEEC, Campinas University, C.P. 6101, 13083-970 Campinas – SP, Brazil. E-mail: [destro@decom.fee.unicamp.br](mailto:destro@decom.fee.unicamp.br).*

<sup>(2)</sup> *Aeronomy Division, Instituto Nacional de Pesquisas Espaciais, CP 515, 12201-970 S.J. Campos – SP, Brazil. E-mail: [eurico@dae.inpe.br](mailto:eurico@dae.inpe.br).*

<sup>(3)</sup> *As (2) above. E-mail: [fabiano@dae.inpe.br](mailto:fabiano@dae.inpe.br).*

<sup>(4)</sup> *School of Electrical Engineering and Computer Science, Ohio University, Athens, OH, 45701, USA. E-mail: [matolak@ohiou.edu](mailto:matolak@ohiou.edu).*

<sup>(5)</sup> *Furnas Centrais Elétricas S/A, Rua Real Grandeza 219, 22283-900 Rio de Janeiro RJ, Brazil. E-mail: [pinhel@furnas.com.br](mailto:pinhel@furnas.com.br).*

## ABSTRACT

This work discusses space weather effects on satellite communications. After presenting trends in mobile satellite communications and signal processing, impacts of space weather are analysed. The article also points out that a partnership between geophysicists and engineers is useful for both physical analysis and management of space weather effects, such as scintillations in satellite/GPS systems; single-event upsets in satellite circuitry, and distortions on signals due to geomagnetic storms.

## INTRODUCTION: TRENDS IN MOBILE COMMUNICATIONS [Eva99]

The Universal Mobile Telecommunication System (UMTS) norm [1] is the major current trend in mobile communications. This norm aims at establishing a global mobile system, wherein any terminal may communicate with any other terminal. The terminals may be located anywhere on the Earth, and the terminals may also be mobile or non-mobile. The deployment of UMTS requires interconnection of several different local telecommunication systems, in order to provide the link between the two terminals. Of course, satellite communications play an important role for UMTS, since they provide cost-effective international links. Moreover, several positioning/navigation systems are based on satellite constellations, such as the GPS and the European Galileo [2]. It should be also pointed out that, in order to cope with the scarcity of transmitting frequencies, the European comission has recently launched a plan for assessing the viability of multimedia and INTERNET data transmission above 30 GHz, by means of satellite links [3].

Three major characteristics of the UMTS are discussed in the following.

(C1) The demand for increasing transmission rates presents challenges to bandwidth management and transceiver processing [1].

(C2) The communication channel is a time-variant system difficult to characterize. In fact, temporal variations may be predicted with limited accuracy, and models are quite dependent on both the spatial and time scale [1]. As a consequence, synchronization between the two communicating terminals is quite problematic, which may be explained by deep fades taking place in the links between mobile users and base stations (either terrestrial or satellite).

(C3) The characterization of mobile channels associated with telecommunication between two aircrafts in flight, or between aircraft in flight and satellites, or even between two satellites, may be considered one of the big challenges for UMTS implementation [4].

Signal processing techniques are important tools applied to cope with (C1)-(C4), particularly the theories applied for the following research topics.

(R1) Analysis of non-stationary signals or time-variant (non)linear systems. In fact, the mobile channel model is well modeled as a time-variant system [5], which is also nonlinear for the case of satellite communications.

(R2) Real-time prediction of non-stationary signals. The main goal is to enable the forecasting of time-variations in the mobile channel, so that the UMTS manager may carry out actions in advance for ensuring system performance and synchronization. Such an idea is the basic principle underlying the concept of "adaptive transmission" [4,6].

(R3) Equalization [7], which corresponds to the digital filtering of the incoming signal at the receiver, in order to overcome impairments imposed by the communication channel on the transmitted signal.

## **EFFECTS OF SPACE WEATHER ON UMTS AND CURRENT SATELLITE COMMUNICATIONS**

The effects of space weather should be considered in the context of the discussions of the previous section. References [8-11] provide a good review in the general effects, as well as concrete examples of the practical interest in the management of space weather influence on technological systems. Related work is also developed in references [12,13], which are excellent reviews focused on satellite communications.

Since geophysical phenomena connected to solar flares are mainly non-stationary [8], space weather effects introduce a new degree of time-variability in signals and systems associated with mobile telecommunications. Of course, according to (C2)-(C3), this not only makes system synchronization still more difficult, but also disturbs aeronautical communications in a special way. The lack of synchronization means that, according to (C1), the huge information exchange rate through the satellite is disrupted, thus blocking communication between terminals of the UMTS. A worst-case influence would be the case of disruptions on spacecraft/satellite telemetry, tracking and control, which could lead to orbit perturbations.

The effects discussed above would be even more serious in Latin America, due to the unusual behavior of the geomagnetic field above some particular areas. For example, in the case of Southeastern part, the regions under the South Atlantic Anomaly (SAA), as well as the equatorial regions, which are subject to the effects associated with the Equatorial anomaly (EA) [14] and with the equatorial electron jet. Notice that ionospheric bubbles impose additional geomagnetic effects on the SAA and EA. It should be stressed that several economic centers of the continent (Buenos Aires, Montevideo, Assuncion, Rio de Janeiro, São Paulo) are located under the SAA. Besides, mineral exploration in the Amazon region (petroleum in Venezuela, mines in Peru) and telemetry of rocket launching basis in Brazil/Guyana (ESA) are also subject to ionospheric bubbles effects. Finally, it should be noticed [15] that almost 70-80% of satellite circuitry failures take place as the satellite flies over the SAA.

On the other hand, the time-variability of space weather signals and systems is a common characteristic with respect of mobile communication signals and systems. As a consequence, one could propose that the theories and methods used in topics (R1)-(R2) would be also useful for space weather research.

In the following, some particular case studies are presented to illustrate the current research and trends in Latin America, particularly in Brazil.

## **SCINTILLATIONS ON SATELLITE AND GPS SYSTEMS [16]**

The INPE (National Space Research Center), Brazil, along with Cornell University, have set up several GPS receivers in the Brazilian territory, in order to evaluate the fluctuations of signal amplitude due to scintillations. In fact, such phenomena disturb seriously the positioning of vessels performing deepwater petroleum exploration [17], as well as deep fades and distortions on other code-division multiple access (CDMA) systems, such as mobile phones and aeronautical communications or navigation [18]. Although all these effects are connected to ionospheric bubbles, experiments [19] carried out in the SAA pointed out also that scintillations may strongly impair commercial satellite communications around 3-10 GHz, especially during the evening.

At the same time, using the same data provided by this network of GPS receivers, it is possible to carry out determination of the Total Electronic Content (TEC) and analyze the behavior of ionosphere during geomagnetic storms in SAA. Current research involves not only these calculations, but also the statistical characterization of fades associated with scintillations in order to mitigate distortions on receivers.

## **SINGLE-EVENT UPSETS IN SATELLITE CIRCUITRY**

Single-event upset (SEU) is an effect associated with high-energy protons flow towards the Earth, which may damage circuits, since the miniaturized VLSI systems are vulnerable to solar particle collision. This is particularly important for Low Earth Orbit (LEO) satellites, which play an important role in the current satellite branch of UMTS. The particle bombardment of memory units may impair software operation due to physical damage or due to the corruption of stored data. For example, the value of one bit located at a place in the memory unit may be changed. This event is called "bit upset" [15]. As a consequence, data corruption at the floating-point unit and in the registers, as well as unexpected operations at the arithmetic and logic units may be observed in microprocessors on-board telecommunication satellites [20].

In fact, according to [15], at least 400 bit upsets per day are expected during a high-solar activity period such as 2000-2003. Of course, this may lead to difficult problems considering that adaptive filters are implemented in microprocessors. Notice that adaptive filters are the basic unities for the implementation of equalizers, and for portions of software radios and adaptive transmission techniques. The authors have already evaluated some of these problems in the context of classical [21] and nonlinear [22] equalizers, and the main conclusion is that SEU lead to poor system performance, since the equalizer can not assure a reasonable signal recovery.

Current research involves consequences of SEU on UMTS, software radio and adaptive transmission schemes. Physical models of SEU effects on microprocessors are needed for analysing system effects, thus requiring interaction with geophysicists.

## **PREDICTION OF GEOMAGNETIC INDEXES AND MITIGATION OF DISTORTIONS DUE TO SOLAR FLARES**

Ionospheric blackout is a big challenge for engineers, since this phenomenon leads to two major problems, which are closely related to the potential effects of geomagnetic storms on UMTS: extremely low signal-to-noise ratio and complete loss of system synchronization. These problems make it almost impossible to employ classical equalization techniques, thus requiring tools specially designed for coping with "almost zero" input power to the equalizer.

Current research involves the study of the magnetospheric model proposed in [23], which is closely related to deconvolution techniques. Since this model is an application of linear prediction theory, the authors consider that the work over time may also lead to new insights on the forecast of geomagnetic indexes. Insights on the use of signal processing for the analysis of geomagnetic-storm time series are also discussed in [24].

## **CONCLUSION**

Whereas geophysicists concentrate their efforts on the comprehension and modeling of the physical phenomena connected to solar flares, satellite engineers devote their energy to mitigating distortions due to the same solar flares [25,26]. Since these distortions could be considered as consequences of the same physical phenomena studied by geophysicists, then it is straightforward to state that the distortions for engineers are exactly the useful information for geophysicists. As a consequence, an interesting partnership could be established, where insights on the physical phenomena would help engineers to build up models in real-time and to propose real-time mitigation techniques, in order to cope with telecommunication impairments. On the other hand, engineers might be useful for space weather research, by providing real-time modeling and forecasting methods [27] to geophysicists. Particularly, signal processing tools associated with analysis and prediction of non-stationary signals seem to be an useful framework for both fields.

The case studies presented in this paper point out the usefulness of the strategy proposed in the last paragraph. At the same time, the main challenge for carrying out the common research seems to be removing boundaries, in order to establish communication between the two research communities, as well as multidisciplinary education initiatives, for example, see [28].

## **ACKNOWLEDGEMENTS**

This work was carried out under financial support of CNPq, Fapesp and CAPES. Special thanks are also addressed to Dr. Aracy M. da Costa (INPE-Brazil) for providing references, as well as to Dr. B. Bavassano (CNR Frascati, Rome, Italy) and Dr. R. Pirjola (FMI, Geophysics Division, Helsinki) for insightful discussions.

## **REFERENCES**

- [1] J.-C. Bie, A. Charbonnier, D. Duponteil, N. Ruelle, S. Tabbane and J.-P. Taisant, "Radiocommunications and

- mobility", *Ann. Télécommun.*, 50, no.1, pp. 114-141, 1995.
- [2] *Proceedings of the IEEE*, Special Issue on Global Positioning System, vol.87, no.1, January 1999.
- [3] <http://www.cost280.rl.ac.uk>
- [4] A. Duel-Hallen, S. Hu, H. Hallen, "Long-range prediction of fading signals", *IEEE Sig. Proc. Magazine*, pp 62-75, May 2000.
- [5] D. W. Matolak, "On the Multi-State Modeling of Mobile Satellite Channels," *Proceedings of MILCOM 2000*, Session 8, October 2000.
- [6] International Telecommunications Union, world wide web site, <http://www.itu.org.>, 2001
- [7] S. Haykin, editor. *Unsupervised adaptive filtering*, vols: 1-2; John Wiley and Sons Inc, USA, 2000.
- [8] D.N. Baker, "Effects of the Sun on the Earth's environment", *Journal of Atmospheric and Solar-Terrestrial Physics*, 62, pp. 1669-1681, 2000.
- [9] J. Lanzerotti, D.J. Thomson and C.G. MacLennan, "Engineering issues with space weather", in *Modern Radio Science 1999*, pp. 25-50, URSI editions, 1999.
- [10] The National Space Weather Program, *The Implementation Plan*, 2nd edition, published by the Office of the Federal Coordinator for Meteorology, Washington, July 2000.
- [11] R. Pirjola, "Geoelectromagnetic disturbances and their effects on technological systems", *EMC*, pp 163-169, Meeting of commission E, Working group 8, Zurich, February 2001.
- [12] D.N. Baker, "Satellite anomalies due to space storms", in *Space storms and space weather hazards*, I.A. Daglis, editor, pp. 285-311, Kluwer Academic Press, the Netherlands, 2001.
- [13] L.J. Lanzerotti, "Space weather effects on communications", in *Space storms and space weather hazards*, I.A. Daglis, editor, pp. 313-334, Kluwer Academic Press, the Netherlands, 2001.
- [14] S.Kumar and A.K. Gwal, "VHF ionospheric scintillations near the equatorial anomaly crest: solar and magnetic activity effects", *J. Atmosf. Sol-Terr. Physics*, vol. 62, no. 3, pp. 157-167, February 2000.
- [15] T. Goka, H. Matsumoto and N. Nemoto, "SEE flight data from Japanese satellites", *IEEE Trans. On Nuclear Science*, vol.45,no.6, pp.2771-2778, Dec. 1998.
- [16] *Proceedings of the IEEE*, Special Issue on Global Scintillation View, vol.70, no.4, April 1982.
- [17] E. de Paula et al., "Ionospheric scintillation effects on DGPS positioning", *Proc. of 6th Internat. Conf. on Geophysics*, Brazilian Geophysical Society, Rio de Janeiro, 1999.
- [18] P.M: Kintner et al, "Fading timescales associated with GPS signals and potential consequences", *Radio Science*, vol. 36, number 4, pp. 731-743.
- [19] A.P. Soares, "Effects of ionospheric bubbles on C-band satellite communications", *Proc. on the Brazilian Symposium in Telecommunications*, September 2001.
- [20] R. Ecoffet et al.; "Space SEE risk assessment for a commercial digital TV receiver", *IEEE Trans. On Nuclear Sciences*, vol. 44, no.6, pp. 2333-2336, Dec 1997.
- [21] J.B. Destro Filho and D. Matolak, "Effects of single-event upsets on satellite communications: issues for blind equalizer design", *Proc. of RADECS'2001*, Grenoble, France, 10-14 September 2001.
- [22] J.B. Destro Filho and J.M.T. Romano, "Influence of parameter initialization on the performance of nonlinear blind equalizers for satellite communications", *Proc. of IEEE/EUROCONi2001*, Bratislava, Slovakia, 5-7 July 2001.
- [23] L.F. Bargatze and D.N. Baker, "Magnetospheric impulse response for many levels of geomagnetic activity", *Journal of Geophysical Research*, vol.90, no. A7, pp.6387-6494, July 1985.
- [24] L.J. Lanzerotti and D.J. Thomson, "Time series data in geophysics/space physics", *Proc. of ICASSP '95*, vol.5, pp 2895-2898, Detroit, USA, May 9-12 1995.
- [25] J.V. Evans, "The past, present and future of satellite communications", in *Modern Radio Science 1999*, pp. 1-24, URSI editions, 1999.
- [26] L.J. Lanzerotti et al, "Engineering issues in space weather", in *Review on Radio Science 96-99*, W. Ross Stone, editor, pp.25-50, URSI and Oxford University Press, 2000.
- [27] Z.Ding and Ye Li, *Blind equalization and identification*, Marcel Dekker Inc., 2000.
- [28] J.B. Destro Filho, J.P. Breda Destro and J.M. Travassos Romano, "Multidisciplinary approaches for signal processing education", *Proc. of IEEE/ISPA '01*, Pula, Croatia, 19-21 June 2001.